

Deluxe Pet Cage Instructions

Deluxe Pet Cages



Pet-Cage-2

1. LAY OUT PARTS TO ENSURE ALL IS THERE.

- | | |
|-------------------|-----------------|
| PARTS:(4) WHEELS | (16) NUTS |
| (4) SMALL SCREWS | (1) FRONT PANEL |
| (12) LARGE SCREWS | (1) BACK PANEL |
| (16) WASHERS | (2) SIDE PANELS |
| (2) BARS | (1) TOP PANEL |
| (1) BOTTOM PANEL | (1) LEAK TRAY |

TOOLS REQUIRED

- SCREW DRIVER
10MM WRENCH

2. ATTACH FRONT, BACK, & SIDES TOGETHER USING (12) LARGE SCREWS, (12) NUTS, & (12) WASHERS.

3. ATTACH TOP TO THE SIDE PANELS USING HARDWARE INCLUDED IN THE TOP PANEL. ONCE SECURED TOP PANEL SHOULD OPEN & CLOSE. ENSURE THE NUT IS IN BETWEEN THE TOP AND THE SIDE PANELS.

4. SECURE (2) BARS TO THE BOTTOM OF THE FRONT & BACK PANELS WITH (4) SMALL SCREWS, (4) WASHERS, & (4) NUTS. THE (1) LEAK TRAY MAY NOW BE INSTALLED.

5. TWIST (4) WHEELS ONTO THE BOTTOM PANEL OF THE DELUXE PET CAGE UNTIL TIGHT.

6. SET (1) BOTTOM PANEL INTO THE DELUXE PET CAGE BY OPENING THE TOP PANEL.

7. CHECK OVER ALL SCREWS & NUTS TO ENSURE A TIGHT FITMENT.

