

**A-2200IEH-XR
Retractable Ramp ATV Lift**

Our A-2200IEH-XR is up to the challenge of lifting all ATV's on the market today. In addition to our New and Innovative retractable ramp system the A-2200IEH-XR has pivot approach ramps that fold out of the way as the lift raises and become wheels stops. Keeping the technician in mind these features limit injury, save time and space which makes your shop area more productive. Our single point hand held pendant fully controls the lift; lifting, lowering into locks and lowering without the use of hands or feet to disengage manual safety latches.



Features

- **NEW!** Retractable Ramp System
- **NEW!** Pivot Approach Ramps
- 47" Rise Height
- 110V Integrated Electric/Hydraulic Power Unit
- Hand Held Control Pendant Six Locking Positions
- Extended 27.5" Long Full Width Approach Ramp
- 50" X 88.6" Table
- **Optional:** Vise, Chock, Dolly Kit

Capacity:	2,200 lbs. (1,000 kg)
Lifting Height, Max:	47.2" (1200 mm)
Height, Min:	7" (180 mm)
Width Overall:	58.5" (1486 mm)
Length Overall:	116.5" (2959 mm) - Fully Lowered
Platform Length:	88.6" (2250 mm)
Platform Width:	50" (1270 mm)
Power Supply:	110V, 60Hz, 1 Phase, 18A
Lifting Time:	30 S
Lowering Time:	30 S
Gross Weight:	980 lbs.